

# 7106



TallyDascom's 7106 direct thermal printer offers reliability, precision and performance in desktop size, where space is limited.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media loading. The clear panel enable simple and effective operation making it very simple to use.

The mechanism uses an all-metal construction ensuring reliable operation, a must for all industrial environments.

## High Performance Desktop Printer

- Space-Saving Design Concept
- Easy and Quick media loading
- Serial and USB Standard
- Supports Zebra® and Datamax® emulation
- Optional Cutter and Peeler
- Internal 5 inch (125mm) media capacity

The 7106 offers a wide range of features and options usually only found on high performance machines. For example, it has an internal power supply providing the most reliable operation and avoiding problems usually associated with external power supplies.

The 7106 is easily integrated into existing systems, internal Ethernet interface is also available. In addition to this, the 7106 is also available with options such as a cutter and a peeler to meet industry requirements.

### Available Configuration:

**7106** Standard Product

SERIAL MATRIX  
PRINTERS

MOBILE  
PRINTERS

THERMAL  
PRINTERS

LINE MATRIX  
PRINTERS

LASER  
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

## 7106

<b>Print Speed</b>	6 ips
<b>Print Width</b>	4.10 inches, 104.1 mm
<b>Print Method</b>	Direct Transfer
<b>Print Length</b>	0.25" to 32" (6.35mm to 812,8 mm)
<b>Resolution</b>	203 dpi:
<b>Font Bitmapped</b>	7 styles, True Type
<b>Printhead Life</b>	50 km or 6 months
<b>Memory</b>	16 Mb SDRAM; 4 Mb Flash
<b>Standard Connectivity</b>	Serial (RS-232C), USB (Version 1.1)
<b>Optional Connectivity</b>	Ethernet LAN (10/100 BaseT), Parallel (IEEE-1284)
<b>Standard Emulation</b>	Auto-switching Zebra ZPL-II and Datamax I-Class, DMX400, Prodigy Plus
<b>Consumables</b>	Thermal direct paper and label
<b>Media Width</b>	0.77" to 4.65" (19.6 mm to 118.1 mm)
<b>Media Length</b>	0.25" to 32" (6.35mm to 812,8 mm)
<b>Roll Diameter</b>	Internally: 5" (125 mm) . Externally 8" with optional holder. Core size 1" - 3" (25 mm to 76 mm).
<b>Indexing</b>	Fully adjustable rear sensor
<b>Barcodes</b>	Standard barcodes include: Code11, Code39, Code93, Code128, I2of5, S2of5, EAN8, EAN13, ANSI CODABAR, LOGMARS, MSI, Plessey, UPC A/E, POSTNET, Planet, Code49, PDF417, CODABLOCK, Maxicode, DataMatrix, QR Code, RSS, TLC39
<b>Physical Weight</b>	3.6 kg
<b>Physical Size</b>	(HxWxD): 183x231x289
<b>Power Voltage</b>	220-240VAC, 50-60Hz
<b>Power Consumption</b>	max 12,9W in Standby, 196W in Operating
<b>Drivers</b>	Windows XP, 2003, Vista, Win 7 (32/64 Bit)
<b>Temperature</b>	+5°C to +35°C
<b>Humidity</b>	30% to 80% (not condensing)
<b>Acoustic</b>	<58dB(A) (ISO 7779)
<b>Options</b>	Auto Cutter, Peeler, Parallel and LAN Interfaces
<b>Note</b>	Accessories Supplied: Head cleaning pen, Start-Up Guide, CD including: Manuals, Drivers and EasyConfig Tool

DASCOM GB Limited  
ViewPoint, Basing View  
Basingstoke, Hampshire. RG21 4RG  
Tel: +44 (0) 1256 481481 • Fax: +44 (0) 1256 481400  
www.dascom.com

SERIAL MATRIX PRINTERS  
MOBILE PRINTERS  
THERMAL PRINTERS  
LINE MATRIX PRINTERS  
LASER PRINTERS