

## T2380

### Powerful & Rugged for Heavy Duty Operation



*Tally*

The T2365 MC and T2380 printers are rugged and powerful high speed matrix printers for heavy duty operation under the most extreme conditions. Reliable, heavy workload output is guaranteed for many years following printer purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

- **Up to 9 part forms**
- **Full range of automatic features to minimize user intervention**
- **Ideal for ' On-Demand' and ' Batch' applications with zero tear for no wasted forms**
- **Straight through paper path for easy forms loading**
- **Parallel and Ethernet (10/100BaseT) standard.**
- **Optional Interfaces: RS232 Serial; Coax/Twinax; Ethernet IPDS**
- **Straight through paper path for easy forms loading**
- **Compatible with a wide range of operating systems including Wiindows, UNIX, DOS, SAP R3 and legacy systems**

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Fully automated operation, coupled with the ,straight through' paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Available Configuration:

- T2380
- T2380 2T with additional rear tractor
- T2380 IGP with IGP/PJL Support

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

THERMAL PRINTERS

LINE MATRIX PRINTERS

LASER PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

# T2380

<b>Print Speed</b>	At 10, 12 cpi: High Speed Draft 800, 1000; Draft 667, 800; NLQ 222, 267
<b>Throughput</b>	627 pages per hour (ECMA 132)
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	750 million characters (draft)
<b>Memory</b>	128Kb
<b>Standard Connectivity</b>	Bi-directional parallel plus Ethernet 10/100BaseT with 128Kb buffer
<b>Optional Connectivity</b>	RS232 Serial, Adapters, Twinax/Coax, Ethernet IPDS
<b>Standard Emulation</b>	IBM® Proprinter, Epson® LQ (ESC P/2), Genicom ANSI, MTPL + Barcode/LCP <b>IGP Version:</b> IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
<b>Optional Emulation</b>	PCL3 (rugged writer)
<b>Fonts</b>	HS Draft, Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, Kix/Royal, OCR A, OCR B, 22 Bar Codes & scaleable LCP
<b>Consumables</b>	Ribbon: 20 million characters
<b>STD Paper Handling</b>	Push tractor with paper parking and AGA; 2nd rear push tractor - T2380-2T only
<b>Optional Paper Handling</b>	2nd front tractor (user installable), paper pedestal, paper basket, paper cutting device
<b>Paper Type</b>	Continuous forms
<b>Paper Weight</b>	60-120gsm
<b>Paper Size</b>	100 to 420mm wide
<b>Physical Weight</b>	Approximately 19Kg
<b>Physical Size</b>	(HxWxD): 280x623x432mm
<b>Power Voltage</b>	230V
<b>Power Consumption</b>	60W printing
<b>Workload</b>	50,000 pages per month
<b>Number of Copies</b>	Up to 6-part forms; 2-part forms for rear tractor of T2380-2T
<b>Temperature</b>	+10° to +35°C
<b>Humidity</b>	20% to 80%
<b>Acoustic</b>	59dB(A)
<b>Warranty</b>	2 years, on-site
<b>Option 1</b>	2nd front tractor (user installable), paper pedestal, paper basket, paper cutting device





**Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOPrior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.**

**DASCOM GB Limited**  
ViewPoint, Basing View,  
Basingstoke, Hampshire RG21 4RG  
Tel: +44 (0) 1256 481481  
Fax: +44 (0) 1256 481400

[www.dascom.com](http://www.dascom.com)

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH  
Ver. 1.0  
Printed Date: 01.04.10

SERIAL MATRIX PRINTERS   
MOBILE PRINTERS   
THERMAL PRINTERS   
LINE MATRIX PRINTERS   
LASER PRINTERS 