

1225





- Compact 24-pin wide carriage printer
- Up to 375 characters per second
- Ideal for front and back office applications
- Auto switching USB and parallel interface
- Long life ribbon



The Tally Dascom 1225 is a 24 pin, 136 column serial dot matrix printer with USB and parallel interfaces as standard. The wide carriage printer is perfect for industrial environments and front and back office applications.

With low running costs, high quality output and an easy to use control panel it's ideal for low volume listing reports, invoices and other critical documents, as well as dispatch notes and labels.

In addition to these applications, the 1225 is also well suited for measurement and control systems.

Amongst the lowest priced matrix printers available today the 1225 also offers a long life ribbon which means fewer ribbon changes, less downtime and lower running costs.

Available Configuration:

1225 Standard Product





1225

Line Density

Memory

Fonts

Printhead life

Consumables

Paper Type

Paper Size

Paper Weight

Number of Copies

Standard Connectivity

Standard Paper Handling

Standard Emulation

Print Speed 10 cpi: 375 cps (HSD), 250 cps (Draft), 83 cps (LQ)

12 cpi: 300 cps (Draft), 100 cps (LQ)

Print Method Serial Impact Dot Matrix Resolution Up to 360 x 360 dpi **Throughput** (ECMA 132) 336 pages per hour **Character Density**

10, 12, 15, 17.1, 20cpi, Proportional Spacing

1, 2, 3, 4, 6, 8 lpi

400 Million Strokes per pin

48 kB

USB 2.0 and parallel (Bi-directional)

Epson LQ (ESC P/2), IBM ProPrinter (2390 Plus)

Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir,

OCR-A/B*, 10 Barcodes

Black Ribbon: 7 million characters Push tractor and single sheet tray

Original +4 (5-part forms) Continuous forms, cut sheet

52-100 gsm

76,2 to 420 mm wide

Physical Weigth 8,5 kg

Physical Size (HxWxD): 173x587x333 mm **Power Voltage** 230 V / 50 to 60 Hz **Power Consumption** max 7,6 W in Stand by

Reliability MTBF 10.000 hours

Windows 2000, 2003 Server, XP, Vista, Windows 7 **Drivers**

Temperature +5°C to +40°C

Humidity 10% to 80% (not condensing)

Acoustic < 55dB(A) (ISO 7779)

NB: For OCR applications it is recommended that your readers are tested with Note

> print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM GB Limited ViewPoint, Basing View

Basingstoke, Hampshire. RG21 4RG

Tel: +44 (0) 1256 481481 • Fax: +44 (0) 1256 481400

www.dascom.com

SERIAL MATRIX PRINTERS MOBILE PRINTERS THERMAL PRINTERS I LINE MATRIX PRINTERS LASER PRINTERS