

1318



Tally DASCOM's 1318 flat-bed serial dot matrix printer, is a 9 pin, 80 column printer with USB and parallel interfaces as standard. The 1318 is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's surgeries where space is limited.

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1318 is ideal for counter-top printing applications such as, tickets, receipts, forms and multipart documents.

Compact in size and low on cost

- Compact 9-pin flat-bed printer
- Up to 240 characters per second
- Ideal for front office applications
- Easy to use
- Long life ribbon
- Small footprint

The long life ribbon of the 1318 means fewer ribbon changes, less downtime and lower running costs.

With print speeds of 240 characters per second (cps) and flexible media handling it keeps transactions smooth and the user happy.

The 1318 is a reliable and easy to use printer, with low running costs and a space saving size.

Available Configuration:

1318 Standard Product

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

1318

Print Speed

10 cpi: 240 cps (HSD), 180 cps (Draft), 45 cps (NLQ)
12 cpi: 200 cps (HSD), 216 cps (Draft), 54 cps (NLQ)

Print Method

Flat-Bed Serial Impact Dot Matrix

Resolution

Up to 144 x 240 dpi

Throughput (ECMA 132)

192 pages per hour

Character Density

10, 12, 15, 17.1, 20cpi, Proportional Spacing

Line Density

1, 2, 3, 4, 6, 8 lpi

Printhead life

400 Million Strokes per pin

Memory

64 kB

Standard Connectivity

USB 2.0 and parallel (Bi-directional)

Standard Emulation

Epson (ESC P/2), IBM 2380+

Fonts

Draft, Roman, Sans Serif, 8 Barcodes

Consumables

Black Ribbon: 7 million characters

Standard Paper Handling

Friction and push tractor

Number of Copies

Original +4 (5-part forms)

Paper Type

Cut sheet and continuous forms

Paper Weight

42-90 gsm

Paper Size

76,2 to 269,2 mm wide

Physical Weight

5,5 kg

Physical Size

(HxWxD): 202x420x342

Power Voltage

230 V / 50 to 60 Hz

Power Consumption

max 7,5 W in Stand by

Reliability MTBF

10.000 hours

Drivers

Windows 2000, 2003 Server, XP, Vista, Windows 7

Temperature

0°C to +45°C

Humidity

10% to 80% (not condensing)

Acoustic

< 49dB(A) (ISO 7779)

Note

NB: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM GB Limited
ViewPoint, Basing View
Basingstoke, Hampshire. RG21 4RG
Tel: +44 (0) 1256 481481 • Fax: +44 (0) 1256 481400
www.dascom.com

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
THERMAL PRINTERS
LINE MATRIX PRINTERS
LASER PRINTERS