

1430





High speed and quality in wide format

- Wide carrigage 24-pin flat-bed printer
- Print speeds up to 450 characters per second
- Ideal for front office applications
- Flexible media handling
- Auto switching USB and parallel interface
- Long life ribbon

Tally DASCOM's 1430 flat-bed seral dot matrix printer, is a 24 pin, 106 column printer with USB and parallel interfaces as standard. The printer is ideal for front office applications in retail outlets, travel agents, train stations and doctor's surgeries where a wide range of media is used.

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1430 is ideal for counter-top printing applications such as, tickets, receipts, forms and multi-part documents.

The long life ribbon of the 1430 means fewer ribbon changes, less downtime and lower running costs.

With print speeds of 450 characters per second (cps) and flexible media handling it keeps transactions smooth and the user happy.

The 1430 is a reliable and easy to use printer, with low running costs and flexible paper management.

Available Configuration:

1430 Standard Product





1430

Throughput (ECMA 132)

Standard Connectivity

Standard Paper Handling

Standard Emulation

Character Density

Print Method

Resolution

Line Density

Memory

Fonts

Printhead life

Consumables

Paper Type

Paper Size

Paper Weight

Number of Copies

Print Speed 10 cpi: 450 cps (HSD), 300 cps (Draft), 100 cps (LQ)

12 cpi: 360 cps (Draft), 120 cps (LQ) Flat Bed Serial Impact Dot Matrix

Up to 360 x 360 dpi 317 pages per hour

10, 12, 15, 17.1, 20cpi, Proportional Spacing

1, 2, 3, 4, 6, 8 lpi

400 Million Strokes per pin

68 kB

USB 2.0 and parallel (Bi-directional)

Epson LQ (ESC P/2), IBM ProPrinter (2390 Plus)

Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir,

OCR-A/B*, 10 Barcodes

Black Ribbon: 7 million characters

Friction and push tractor
Original +7 (8-part forms)
Cut sheet , continuous forms

52-157 gsm

51 to 304,8 mm wide

Physical Weigth 7,5 kg

Physical Size(HxWxD): 202x495x342Power Voltage230 V / 50 to 60 HzPower Consumptionmax 3,5 W in Stand by

Reliability MTBF 10.000 hours

Drivers Windows 2000, 2003 Server, XP, Vista, Windows 7

Temperature $+5^{\circ}\text{C} \text{ to } +35^{\circ}\text{C}$

Humidity 10% to 80% (not condensing)

Acoustic < 55 dB(A) (ISO 7779)

NoteNB: For OCR applications it is recommended that your readers are tested with

print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM GB Limited ViewPoint, Basing View Basingstoke, Hampshire. RG21 4RG

Tel: +44 (0) 1256 481481 • Fax: +44 (0) 1256 481400

www.dascom.com

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
THERMAL PRINTERS
LINE MATRIX PRINTERS
LASER PRINTERS