

7206



Tally
DASCOM

High Performance Desktop Printer

- Space-Saving Design Concept
- Easy and Quick media loading
- Serial and USB Standard
- Supports Zebra® and Datamax® emulation
- Optional Cutter and Peeler
- Internal 5 inch (125mm) media capacity

The TallyDascom 7206 thermal transfer models offer industrial performance in desktop size. The mechanism uses an all-metal construction ensuring reliable operation, a must for all industrial environments.

The user friendly design of the printers allows a space saving vertical opening and an easy to use print mechanism ensures quick and easy loading of labels and ribbons. An intelligent ribbon control system stops the ribbon from wrinkling, giving you constant height print quality.

The 7206 offers a wide range of features and options usually only found on high performance machines. The 7206 is easily integrated into existing systems, internal Ethernet interface is also available.

In addition to this, the 7206 is also available with options such as a cutter and a peeler to meet industry requirements.

The 7206-300 with a resolution of 300 dpi is ideal for printing labels with logos, images and graphics.

Available Configuration:

7206 Thermal Transfer—203 dpi Product

7206-300 Thermal Transfer— 300 dpi Product

7206

Print Speed	6 ips
Print Width	4.10 inches, 104.1 mm
Print Method	Direct or Thermal Transfer
Print Length	0.25" to 32" (6.35mm to 812.8 mm)
Resolution	203 dpi / 300dpi model available
Font Bitmapped	7 styles, True Type
Printhead Life	50 km or 6 months
Memory	16 Mb SDRAM; 4 Mb Flash
Standard Connectivity	Serial (RS-232C), USB (Version 1.1)
Optional Connectivity	Ethernet LAN (10/100 BaseT), Parallel (IEEE-1284)
Standard Emulation	Auto-switching Zebra ZPL-II and Datamax I-Class, DMX400, Prodigy Plus
Consumables	Ribbon, thermal transfer paper/labels, direct thermal paper/labels
Media Width	0.77" to 4.65" (19.6 mm to 118.1 mm)
Media Length	0.25" to 32" (6.35mm to 812.8 mm)
Roll Diameter	Internally: 5" (125 mm) . Externally 8" with optional holder. Core size 1" - 3" (25 mm to 76 mm).
Indexing	Fully adjustable rear sensor
Ribbon Type	Ink side in or out. Wax, Wax/Resin or Resin Type
Ribbon Length	2.9" (74 mm) maximum diameter, 360meter length, 1" cores
Barcodes	Standard barcodes include: Code11, Code39, Code93, Code128, I2of5, S2of5, EAN8, EAN13, ANSI CODABAR, LOGMARS, MSI, Plessey, UPC A/E, POSTNET, Planet, Code49, PDF417, CODABLOCK, Maxicode, DataMatrix, QR Code, RSS, TLC39
Physical Weight	4,5 kg
Physical Size	(HxWxD): 270x231x289
Power Voltage	220-240VAC, 50-60Hz
Power Consumption	max 13W in Standby, 159W in Operating
Drivers	Windows XP, 2003, Vista, Win 7 (32/64 Bit)
Temperature	+5°C to +35°C
Humidity	30% to 80% (not condensing)
Acoustic	<58dB(A) (ISO 7779)
Options	Auto Cutter, Peeler, Parallel and LAN Interfaces
Note	Accessories Supplied: Ribbon sample, Ribbon core, Ribbon handles, Head cleaning pen, Start-Up Guide, CD including: Manuals, Drivers and EasyConfig Tool.

DASCOM GB Limited
ViewPoint, Basing View
Basingstoke, Hampshire. RG21 4RG
Tel: +44 (0) 1256 481481 • Fax: +44 (0) 1256 481400 • www.dascom.com

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
THERMAL PRINTERS
LINE MATRIX PRINTERS
LASER PRINTERS