

PP 205

The Compact And Economical Matrix Printer For Logistics, Industry And Administration



The PP 205 provides for the economic access to professional dot matrix printing.

- Heavy Duty
24-wire dot matrix printer
- Compact, modern design
- High throughput
 - 448 cps (10 cpi)
 - 319 pages/hour
- 2 paper inputs for fanfold and cut sheet processing
- Up to 5 copies (1+4)
- Precise print positioning
- 9 scalable fonts
- Perfect barcode printing

TECHNICAL DATA

Printer Specification

Technology:	serial impact dot matrix
Printhead:	24 wires, 0.2 mm (0.01 inch) needle diameter; lifetime 400 million characters per minute (per wire)
Print mode	High Speed Draft (HSD), Draft Quality (DQ), Near Letter Quality (NLQ) und Letter Quality (LQ)
Print format:	136 columns at 10 cpi
Ribbon:	nylon ribbon cassette, black, more than 5 million characters
Dimensions:	570 x 330 x 120 mm (WxDxH) (22.4 x 13 x 4.72 inch)
Weight:	Approximately 9,7 kg (19 lb)
Diagnostics:	selftest, hexdump
Operator Panel:	5 pushbutton switches, 2 modes, 6 LEDs indicators, 1 buzzer
Rated Voltage:	100 - 120 VAC \pm 10% / 220 - 240 VAC \pm 10% 50 - 60 Hz
Power input:	max. 180 W, Standby max. 10 W
Environmental conditions:	operating: + 5 to +38°C (+50 to +100° F) 30 bis 80% rel. humidity storage: -15 to +60 °C (+5 to +140 ° F) 10 to 90% rel. humidity
Noise level:	max. 49 dB(A) acc. to ISO 7779
Agency approvals:	UL/CSA, TÜV, FCC-B, CNS-B

Performance

Print speed:	HSD: 448 cps at 10 cpi DQ: 360 cps at 10 cpi NLQ: 225 cps at 10 cpi LQ: 113 cps at 10 cpi
Throughput:	DQ: 319 pages/hour LQ: 172 pages/hour
Duty cycle:	8.000 pages per month
MTBF:	20.000 hours at 25% duty cycle

Paper Handling

Paper input:	Fanfold paper: push tractor with park position Cut sheet: Friction Feed, top in, top out
Paper output:	rear side, zero-tear-off
Paper weight:	Up to 280 g/m ²
Paper width:	Fanfold paper 102 to 420 mm (4.0 to 16.5 inch), Cut sheet 102 to 420 mm (4.0 to 16.5 inch)
Paper length:	Fanfold over 102 mm (4.0 inch) Cut sheet 76 to 420 mm (3.0 to 16.5 inch)
Form feed:	5,6 inch/second
Copies:	1 original + 4 copies; max. paper thickness 0.35 mm (0.01 inch)

Connectivity

Interfaces:	Parallel Centronics, USB, optional: LAN-card (Ethernet 10/100) as plug-in
Emulations:	Epson ESC/P2 IBM Proprinter XL24 (AGM), Fujitsu DPL24C PLUS
Buffer:	up to 128 KByte
Character sets:	Italic character set Graphic character sets 1 and 2 IBM PS/2 character set, code page 437, 850, 852, 855, 860, 863, 865, 866 and DHN IBM 437 and 851 ISO 8859-1 and ECMA 94 61 national character sets
National character sets (all emulations.):	Code pages 437, 850, 851, 852, 855, 860, 862, 863, 865, 866, ISO 8859-1, ECMA 94, USA, UK, German, French, Italian, Spanish, Swedish, Finnish, Norwegian, Danish 1 and 2, Hungarian 1 and 2, Slovenian 1 and 2, Mazovia 1 and 2, Polish 1 and 2, Latin 2 1 and 2, Latin P, PG-DHN, ELOT 927, Lithuanian 1 and 2, MIK, Macedonian, PG-MAC, ABY, ABG, DEC GR, GREEK 11, HBR-OLD, HBR-DEC, ISO Turkish, ISO Latin, Kamenicky 1 and 2, Turkish 1 and 2, ELOT 928, Cyrillic, RUSCII, Latin-9 (Note: Some national character sets do not support some resident fonts.)
Resident fonts:	Letter Quality
- Bitmap fonts:	Courier 10, Pica 10, Prestige Elite 12, Boldface PS, Compressed, Draft 12, High-speed draft 12, OCR-B 10, OCR-A 10, Correspondence 10
- Scalable fonts:	Courier (upright, italic, bold) Nimbus Sans (upright, italic, bold) Timeless (upright, italic, bold)
Character attributes:	Bold, shadow, double-width, double-height, con- densed, superscript, subscript, underlining, justified and proportional. Other modes, such as italic, multi size, outlined, shaded, and overlay, are available depending on the emulation used.
Pitches:	10, 12, 15, 17.1, 18 und 20 characters/inch, propor- tional
Line spacing:	1, 2, 3, 4, 5, 6, 7 or 8 lines/inch Programmable in 1/360 inch and other increments for image graphics
Barcodes:	Code 3 of 9, UPC-A, UPC-A with check character, Codabar (NW7), EAN13, EAN8, Industrial 2 of 5, Matrix 2 of 5, Interleaved 2 of 5, Code 128
Graphics:	max. 360 x 360 dpi

Printer drivers for Windows 3.x/95/98/NT 4.0 /2000/XP are available for
download at www.psiprinters.com.



Cut sheet printing with
the PP 205.

Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.

PSi Printer Systems international GmbH

Eiserfelder Straße 316
D - 57080 Siegen

Tel: +49 (0)271 / 3597 - 102 e-mail sales@psi-si.de
Fax: +49 (0)271 / 3597 - 190 <http://www.psiprinters.com>

