

T2248

Nimble, quiet workhorse



Tally

High-speed printing - At 10 cpi, print speed ranges from 113 cps for letter quality to 432 cps for high speed draft quality. A 24 pin print head offers high speed with excellent quality.

Software compatibility - Compatible with the IBM Proprinter XL24E and Epson ESC/P2 command sets.

Multiple fonts - The printer has nineteen resident fonts: Ten bitmap fonts - Courier 10, Pica 10, Prestige Elite 12, Boldface PS, OCR-B, OCR-A, Correspondence, Compressed, Draft and High-speed Draft, and nine outline fonts - Timeless, Nimbus Sans and Courier, each in upright, italic and bold.

- 80 column
- Auto tear off
- Auto load
- Printhead protection
- USB interface (model option)
- Lan interface (model option)
- Parallel and Serial interfaces standard
- Auto interface switching on multiple I/F versions

Large print buffer - 128k bytes are available in total for strong input data and downloading fonts. A large input data buffer allows you to send files to the printer and return quickly to your application.

Simple switching of paper types & Auto tear-off - Parking continuous forms makes it easy to switch between continuous forms and single sheets. Continuous forms are automatically fed up to the tear-off position at the end of each job.

Maintenance free - Periodic cleaning and changing the ribbon cartridge are all that's required.

Available Configuration:

Parallel/USB
Ethernet 10Base-T/100Base-T

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

T2248

Print Speed	10 cpi: 432 (High speed draft), 360 (Draft), 113 (LQ)
Resolution	Graphics 360X360 DPI (ESC/P Emulation only)
Printhead Life	200 million characters
Memory	128Kb
Standard Connectivity	(model variants) Parallel/USB; Ethernet 10BaseT/100Base-T (t.b.a.)
Standard Emulation	Epson ESCP/P2, IBM XL24E
Fonts	Bitmap fonts: Courier 10, Prestige Elite 12, Boldface PS, Compressed, Draft 12, High-speed draft 12, OCR-B 10, OCR-A 10, Correspondence 10, PCIA 10; Scaleable Fonts: Courier, Nimbus Sans®, Timeless (Normal, Bold, Italic)
Consumables	Ribbon: 4 million characters
STD Paper Handling	Auto-tear; manual continuous/cut sheet switch; manual paper thickness adjustment
Paper Type	Continuous forms, cut sheets
Paper Weight	Approximately 7.3 Kg (16 lbs.)
Paper Size	Cut sheet: width 102-267 mm, length 76-364 mm Continuous forms: width 102-267 mm length over 102 mm)
Physical Weight	Approximately 7.3 Kg (16 lbs.)
Physical Size	(WxDxH) 415 x 330 x 120 mm
Power Voltage	220 VAC to 240 VAC +10%
Power Consumption	10W max waiting, 70W max average, 180W max
Workload	8,000 pages per month
Number of Copies	Up to 5 part forms
Temperature	5 °C to 35 °C Humidity 20 -80% RH
Humidity	20 - 80% RH
Acoustic	49 dBa
Warranty	2 years, return to base
Option 1	Ethernet 10Base-T / 100Base-T; USB ver. 1.1 Type B

DASCOM GB Limited
ViewPoint, Basing View,
Basingstoke, Hampshire RG21 4RG
Tel: +44 (0) 1256 481481
Fax: +44 (0) 1256 481400

www.dascom.com

All company and product names are trademarks or registered trademarks of their respective owner.
Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH
Ver. 1.0
Printed Date: 01.04.10

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
THERMAL PRINTERS 
LINE MATRIX PRINTERS 
LASER PRINTERS 