

T2340/24 & T2340/9

The Ultimate In Document Printing



Tally

DASCOM's mid range serial matrix printers include the T2240/T2340 series products. Very popular transaction printers, they feature great ergonomics. Forms are easy to load as the paper's installed at the front, not the rear. With automatic top of form and zero tear the printers are easy to set up with no wasted forms.

The products are ideal for back office applications which include retail, local government, hospitals, warehousing and ditribution. They include printing labels, shipping documents and multipart forms.

- **High quality 9 and 24 pin printhead**
- **Narrow (80 columns - T2240) and wide format versions (136 columns - T2340) available**
- **Front feed for easy paper loading and reliable paper transport**
- **Zero tear, paper park, automatic top of form for ease of use**
- **Wide range of emulations for easy connection to a wide range of hosts**
- **Manual feed: front in, front out; ideal for cheques, statements, registration cards**

Both 9 and 24 pin models are available for different print quality requirements; narrow and wide format machines offer the choices of small footprint and diverse range of forms.

In line with market demands, the new printers are quieter and easier to use than competitive products in their class. All products support graphics and barcodes.

Available Configuration:

T2340/24 24 pin version
T2340/9 9 pin version

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

T2340/24 & T2340/9

Print Speed	9 wire printhead: At 10 cpi; Draft: 413 cps, Copy Draft 310 cps, NLQ: 77 cps 24 wire printhead: At 10 cpi; Draft: 409 cps, Copy Draft 275 cps, NLQ: 92 cps
Throughput	T2x40/9: Letter Performance 363; Spreadsheet 185. T2x40/24: Letter Performance 368; Spreadsheet 175.
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	3, 4, 6, 8, 12 lpi
Printhead Life	300 million characters (draft)
Memory	64Kb
Standard Connectivity	Parallel (Bi-directional)
Optional Connectivity	Serial RS232, external ethernet 10/100baseT, USB - parallel adapter
Standard Emulation	9 pin: MTPL, IBM ProPrinter XL, Epson FX850+/FX1050 + barcodes. 24 pin: MTPL, IBM ProPrinter XL24e, Epson LQ850+/LQ1050+/Esc PEpson® ESC/P2
Fonts	9 pin: Draft, Draft Copy, Quadrato, Courier. 24 pin: Draft, Draft Copy, Courier, Roman, Sans Serif, Prestige Elite, Script, OCR-A/B*, 13 barcodes, scaleable LCP fonts for 9 + 24 pin machines OCR-A, 10 barcodes for 9 + 24 pin machines
Consumables	Ribbon: 4 million characters
Standard Paper Handling	Tractor paper - push tractors with paper parking, view and tear at top of form cut sheet front insertion with integrated table
Optional Paper Handling	2nd push tractor
Paper Type	Continuous forms and cut forms
Paper Weight	Continuous Forms 60-120gsm. Cut sheet 80-120gsm
Paper Size	76 to 420mm wide
Physical Weight	9 pin: 9Kg; 24 pin: 11Kg
Physical Size	(HxWxD): 200 x 625 x 245mm
Power Voltage	230V
Power Consumption	55W printing
Workload	14,000 pages per month
Number of Copies	9 Pin: 1+5 Standard, 1+6 Heavy Mode; 24 Pin: 1+3 Standard, 1+4 Heavy Mode
Acoustic	9 pin: 54dB(A); 24 pin: 53dB(A)
Warranty	2 years, return to base
Option 1	Push tractors, front; automatic cut sheet feeder, front

Note: Exceeding the monthly duty cycle will not void the warranty if DASCOM consumables and maintenance kits are used.

DASCOM GB Limited
ViewPoint, Basing View,
Basingstoke, Hampshire RG21 4RG
Tel: +44 (0) 1256 481481
Fax: +44 (0) 1256 481400

www.dascom.com

All company and product names are trademarks or registered trademarks of their respective owner.
Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH
Ver. 1.0
Printed Date: 01.04.10

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
THERMAL PRINTERS 
LINE MATRIX PRINTERS 
LASER PRINTERS 